



ABC FLEX

Fabrication de gaines flexibles techniques

ABC PUR F 5

Gaine pour aspiration de poussières abrasives

Suction hose for abrasive dusts


Absaugschlauch für abrasive Stäube



Polyuréthane anti-abrasion épaisseur 0,5 mm, transparent. Spirale en acier ressort cuivré.
Abrasion resistant polyurethan, thickness 0,5 mm, translucent. Coppered spring steel wire.
Abriebfestes Polyurethan, Dicke 0,5 mm, lichtdurchlässig. Verkupferter Federstahldraht.

Température -40 à +90°C

Lg standard 10 m.

Accessoires. Accessories. Zubehör. 


Caractéristiques à 20°C. Data at 20°C. Daten um 20°C.

Sous réserve de modifications. Data subject to modifications. Änderungen vorbehalten.

ABC PUR F 5



DN d. i.	Pression de service bar	Tenue aspiration bar	R courbure mm	D extérieur mm	Poids kg/m
DN i. d.	Working pressure bar	Underpressure bar	Bending R mm	Outer D mm	Weight kg/m
DN iD	Betriebsdruck bar	Unterdruck bar	Biegeradius mm	Außen-D mm	Gewicht kg/m
38	0,850	0,250	20	44	0,26
40	0,820	0,240	20	46	0,28
50	0,780	0,201	25	57	0,30
60	0,760	0,186	35	68	0,35
65	0,680	0,157	38	73	0,38
70	0,610	0,157	40	78	0,41
75	0,610	0,127	43	83	0,50
80	0,530	0,127	45	88	0,53
90	0,460	0,093	50	99	0,65
100	0,460	0,093	55	108	0,67
110	0,300	0,093	60	119	0,73
120	0,300	0,093	65	129	0,79
125	0,300	0,093	68	134	0,83
140	0,300	0,064	75	149	0,86
150	0,300	0,064	80	159	0,89
160	0,300	0,064	85	169	1,05
170	0,230	0,064	90	179	1,09
175	0,230	0,064	93	184	1,11
180	0,230	0,064	95	189	1,13
200	0,230	0,064	105	210	1,25
225	0,150	0,029	118	235	1,41
250	0,150	0,029	130	260	1,49
275	0,150	0,029	143	285	1,64
280	0,150	0,029	145	290	1,67
300	0,140	0,028	155	310	1,78
315	0,130	0,026	162	325	1,85
350	0,120	0,025	180	360	2,44
400	0,120	0,025	210	410	3,04

Accessoires. Accessories. Zubehör. 

Caractéristiques à 20°C. Data at 20°C. Daten um 20°C.

Sous réserve de modifications. Data subject to modifications. Änderungen vorbehalten.

ABC PUR F 5